




Draka

DXPCD Chemical Resistant Cable

for burial / loose tube construction / 2 to 144 fibers / singlemode or multimode / OFC



Application

These are multiple fiber loose tube cables designed for high-speed interbuilding communication systems including long haul networking, interbuilding trunking and local loop applications, either in tray installations, above or below ground in conduit or directly buried. Steel armor and a second jacket of heavy duty CPE resist attack by chemicals and petroleum derivatives as well as provide extra strength for direct burial and resistance to rodent attack. Loose tube design offers optimum fiber performance.

Fully flooded and higher fiber count cables are available. All DXPCD cables are Gigabit Ethernet IEEE 802.3z compliant. MaxCap multimode fiber for 10 Gb networks is available.

Features

1. FIBER

Multimode or singlemode fibers with an acrylate coating for mechanical protection colored per TIA/EIA 598

2. BUFFER TUBES

Polymeric insulation filled with a moisture-resistant material to prevent water penetration. Fillers (when needed) are dielectric material.

3. CENTRAL STRENGTH MEMBER

Dielectric material (epoxy/fiberglass rod).

4. DRY BLOCK TAPE

Swellable tape wrapped around the cable core to prevent water penetration.

5. STRENGTH MEMBER

Aramid yarn.

6. INNER JACKET

Black heavy duty CPE

7. DRY BLOCK TAPE

Swellable tape wrapped around the cable core to prevent water penetration.

8. ARMOR

Corrugated steel tape formed over the inner jacket and bonded to the outer jacket.

9. OUTER JACKET

Black heavy duty CPE

Ratings

OFC



DXPCD Chemical Resistant Cable

for burial / loose tube construction / 2 to 144 fibers / singlemode or multimode / OFC

Part Number	Installation Pull Strength Lbs (Newtons)	Installation Bend Radius in (cm)	Operating Tension Lbs (Newtons)	Operating Bend Radius in (cm)	Vertical Rise feet (meters)	Cable O.D. in (mm)	Approx. Cable Weight Lbs/Mft (Kg/Km)
DXPCD2-02R-XXY	600 (2700)	13.0 (33.0)	200 (890)	9.8 (24.8)	860 (262)	0.650 (16.51)	186 (277)
DXPCD4-04-XXY	600 (2700)	13.0 (33.0)	200 (890)	9.8 (24.8)	860 (262)	0.650 (16.51)	86 (277)
DXPCD6-06-XXY	600 (2700)	13.0 (33.0)	200 (890)	9.8 (24.8)	860 (262)	0.650 (16.51)	186 (277)
DXPCD4-08-XXY	600 (2700)	13.0 (33.0)	200 (890)	9.8 (24.8)	860 (262)	0.650 (16.51)	86 (277)
DXPCD6-12-XXY	600 (2700)	13.0 (33.0)	200 (890)	9.8 (24.8)	860 (262)	0.650 (16.51)	186 (277)
DXPCD4-16-XXY	600 (2700)	13.0 (33.0)	200 (890)	9.8 (24.8)	860 (262)	0.650 (16.51)	86 (277)
DXPCD6-24-XXY	600 (2700)	13.0 (33.0)	200 (890)	9.8 (24.8)	860 (262)	0.650 (16.51)	86 (277)
DXPCD6-30-XXY	600 (2700)	13.0 (33.0)	200 (890)	9.8 (24.8)	860 (262)	0.650 (16.51)	86 (277)
DXPCD6-36-XXY	600 (2700)	13.8 (35.1)	200 (890)	10.4 (26.3)	808 (246)	0.690 (17.53)	198 (295)
DXPCD12-48-XXY	600 (2700)	13.8 (35.1)	200 (890)	10.4 (26.3)	758 (231)	0.690 (17.53)	211 (314)
DXPCD12-60-XXY	600 (2700)	13.8 (35.1)	200 (890)	10.4 (26.3)	758 (231)	0.690 (17.53)	211 (314)
DXPCD12-72-XXY	600 (2700)	14.6 (37.0)	200 (890)	11.0 (27.8)	693 (211)	0.730 (18.54)	231 (344)
DXPCD12-84-XXY	600 (2700)	15.4 (39.1)	200 (890)	11.6 (29.3)	635 (194)	0.770 (19.56)	252 (375)
DXPCD12-96-XXY	600 (2700)	16.2 (41.1)	200 (890)	12.2 (30.9)	580 (177)	0.810 (20.57)	276 (411)
DXPCD12-108-XXY	600 (2700)	17.4 (44.2)	200 (890)	13.1 (33.1)	537 (164)	0.870 (22.10)	298 (443)
DXPCD12-120-XXY	600 (2700)	18.6 (47.2)	200 (890)	14.0 (35.4)	485 (148)	0.930 (23.62)	330 (491)
DXPCD12-132-XXY	600 (2700)	18.6 (47.2)	200 (890)	14.0 (35.4)	444 (135)	0.930 (23.62)	360 (536)
DXPCD12-144-XXY	600 (2700)	19.8 (50.3)	200 (890)	14.8 (37.7)	398 (121)	0.990 (25.15)	402 (598)

Flooded core is available. Higher fiber counts are available.

The data herein is approximate and subject to normal manufacturing tolerances.

Information is subject to change without notice. Consult factory for a variety of alternate constructions for specific applications.

Fiber Performance

Replace XXY in the above part number with your fiber requirements:

Multimode Designation	Min. Bandwidth 850nm/1300nm	Max. Attenuation 850nm/1300nm
50GBE	1500/500	3.50/1.50
50H	500/500	3.50/1.50
50E1 (HiCap)	500/500	3.50/1.00
62X	200/500	3.50/1.00
62E1	300/600	3.50/1.00*

* Mode conditioning patch cords not required

Single Mode Designation	Max. Attenuation 1310nm/1550nm
010X	0.40/0.30
010A3	0.35/0.25

Environmental Specifications

Description	FOTP	Requirements
Operating Temp	EIA-455-3	-40°C to 80°C
Storage Temp	EIA-455-3	-40°C to 80°C
Installation Temp	---	-20°C to 80°C

Mechanical Specifications

Description	FOTP	Requirements
Crush Resistance	EIA-455-41	1225 N/cm (700 lbs/in)
Impact Resistance	EIA-455-25	25 impacts with 5.0 N-m

Draka Engineered Specialties

22 Joseph E. Warner Blvd. | North Dighton, MA 02764 | Tel +1-508-822-5444

761 Joseph E. Warner Blvd. | Taunton, MA 02780 | Tel +1-508-822-5444

One Tamaqua Blvd. | Schuylkill Haven, PA 17972 | Tel +1-570-385-4381

For sales and technical information, contact:

Draka Engineered Specialties | 1-800-233-3190 | 1-570-385-4381 | 1-570-385-1092 fax | www.drakausa.com